

# EG-Konformitäts - Erklärung EC-Homologation Declaration

im Sinne der EG-Richtlinie Maschinen 98/37/EG, Anhang II A  
in the sense of EC directive on machines 98/37/EEC, annex II A

Die Bauart der Maschine / Type of machine

**ROLL-TRAILERS 40' / 100 TONS**

TSS-Nr. / TSS-no.

**A 5016**

from **FRGC 100081-6**

to **FRGC 100105-2**

entwickelt, konstruiert und gefertigt in Übereinstimmung mit den  
developed, designed and manufactured according to

*EG-Maschinen Richtlinien (98/37/EG)*

Folgende harmonisierte Normen sind angewandt:

The following national standards, directives and specifications have been applied:

*DIN EN 287-1*

*(Prüfung von Schweißern, Schmelzschweissen, Teil 1: Stähle)*

*DIN EN 292*


*(Sicherheit von Maschinen, Grundbegriffe, allgemeine Gestaltungsleitsätze)*

Folgende nationale Normen, Richtlinien und Spezifikationen sind angewandt:

The following national standards, directives and specification have been applied

*BGV D 27 (VBG 36)*

TSS declares their exclusively responsibility.

**Transport Systems Seacom AG**  
  
P.O. BOX 1481  
CH-8201 SCHAFFHAUSEN  
TEL. +41 52 692 04 00  
FAX +41 52 692 04 09

Eduard Schellenberg

Schaffhausen, 26th May 2004

TSS AG  
Schaffhausen

### Rolltrailer 40' – 100 Ton

#### Technical Specifications

- *Dimensions : 12.300 x 2.600 x 750 / 800 mm*
- *Platform :*
  - *timber 50 mm, impregnated, steel plate above running gear*
  - *4 corners rounded, and painted in yellow*
- *Running gear :*
  - *2 rockerbeams 42 Ton*
  - *4 oscillating axles 140 x 140*
  - *rockerbolt 120 Ø / axle bolt 90 Ø*
  - *8 solid rubber tyres 22 x 16 x 16 with conical roller bearings (enclosed mounting; greasing nipples foreseen AND needed for conical bearings)*
  - *make tyres: Solideal*
  - *make rims: produced in Polish factory*
  - *steel wheelcaps*
- *Accessories :*
  - *16 lashing points MBL 32 Ton*
  - *safety – coupling*
  - *forklift pockets*
  - *6 collapsible container twistlocks*
  - *20 stanchion pockets*
  - *platform reinforced for empty stacking of trailers*
  - *signwriting*
- *Finish :*
  - *trailer shotblasted after assembly to SA 2 ½*
  - *zinc phosphate primer*
  - *alcyd-resin top coat; Grimaldi color RAL1007(when different: to be specified)*
  - *total dft 100-120 my*